

SK22/SS22~SK220/SS220

2.0Amp Surface Mount Schottky Barrier Rectifiers

Features

- ◆ The plastic package carries Underwriters Laboratory Flammability Classification 94V-0
- ◆ For surface mounted applications
- ◆ Metal silicon junction,majority carrier conduction
- ◆ Low power loss,high efficiency
- ◆ Built-in strain relief,ideal for automated placement
- ◆ High forward surge current capability
- ◆ High temperature soldering guaranteed:
260°C/10 seconds at terminals

Mechanical Data


Case : JEDEC DO-214AB molded plastic body

Terminals: leads solderable per MIL-STD-750, Method 2026

Polarity: Color band denotes cathode end

Mounting Position: Any

Weight : 0.007 ounce, 0.25 grams



Maximum Ratings And Electrical Characteristics

Ratings at 25°C ambient temperature unless otherwise specified. Single phase half-wave 60Hz,resistive or inductive load, for capacitive load current derate by 20%.

| | SYMBOLS | SK22 SS22 | SK23 SS23 | SK24 SS24 | SK25 SS25 | SK26 SS26 | SK28 SS28 | SK210 SS210 | SK215 SS215 | SK220 SS220 | UNITS |
|---|-----------------|--------------|--------------|--------------|--------------|--------------|--------------|----------------|----------------|----------------|-------|
| Maximum repetitive peak reverse voltage | V_{RRM} | 20 | 30 | 40 | 50 | 60 | 80 | 100 | 150 | 200 | VOLTS |
| Maximum RMS voltage | V_{RMS} | 14 | 21 | 28 | 35 | 42 | 56 | 70 | 105 | 140 | VOLTS |
| Maximum DC blocking voltage | V_{DC} | 20 | 30 | 40 | 50 | 60 | 80 | 100 | 150 | 200 | VOLTS |
| Maximum average forward rectified current at T_L (see fig.1) | $I_{(AV)}$ | 2.0 | | | | | | | | Amps | |
| Peak forward surge current 8.3ms single half sine-wave superimposed on rated load (JEDEC Method) | I_{FSM} | 50.0 | | | | | | | | Amps | |
| Maximum instantaneous forward voltage at 2.0A | V_F | 0.55 | | 0.70 | | 0.85 | | 0.95 | | Volts | |
| Maximum DC reverse current $T_A=25^\circ C$ at rated DC blocking voltage $T_A=100^\circ C$ | I_R | 0.5 | | | | 0.2 | | | | mA | |
| Typical junction capacitance (NOTE 1) | C_J | 220 | | 180 | | | | pF | | | |
| Typical thermal resistance (NOTE 2) | $R_{\theta JA}$ | 75.0 | | | | | | | | °C/W | |
| Operating junction temperature range | $T_J,$ | -65 to +125 | | | | -65 to +150 | | | | °C | |
| Storage temperature range | T_{STG} | -65 to +150 | | | | | | | | °C | |

Note:1.Measured at 1MHz and applied reverse voltage of 4.0V D.C.

2.P.C.B. mounted with 0.2x0.2"(5.0x5.0mm) copper pad areas